



FHO3300Plus Series OTDR

- 6.2-inch capacitive touch screen
- Event deadzone/attenuation deadzone: 1m/4m
- Support VFL, OPM, OLS, RJ45(RJ45 sequence, length and tracking) and FLM function
- 5000mAh lithium battery
- Support Bluetooth, and mobile phone app

Items	Specifications
Pulse Width	3ns, 5ns, 10ns, 30ns, 50ns, 100ns, 275ns, 500ns, 1us, 2us, 5us, 10us, 20us
Distance Range	100m~260km
Sampling Resolution	Minimum 5cm
Sampling Points	Maximum 256,000 points
Linearity	≤0.03dB/dB
Loss Threshold	0.01dB
Loss Resolution	0.001dB
Distance Resolution	0.01m
IOR Setting	1.0000~2.0000, 0.0001 step
Distance Accuracy	±(0.75m+test distance×3×10 ⁻⁵ +sampling resolution) (excluding IOR uncertainty)

Items	Specifications
Visual Fault Locator	
Working Wavelength	650nm±20nm
Output Power	10mw
Launching Mode	CW/1Hz/2Hz
Connector	Universal 2.5mm
Optical Power Meter	
Wavelength Range	800~1700m
Calibrated Wavelength	850/1270/1300/1310/1490/1550/1577/1625/1650nm
Test Range	-40~+26dBm; (-60~+6dBm is optional)
Accuracy	±0.5dB
Resolution	0.01dB



10G PON Selective Optical Power Meter	
Calibrated Wavelength	850/1270/1300/1310/1490/1550/1577/1625/1650nm
10G PON Optical Power Meter	1490nm/1577nm Separate measurements and display on the same screen
Test Range	-40~+10dBm
Accuracy	±0.5dB
Optical Laser Source	
Working Wavelength	Consistent with OTDR
Output Power	> -8dBm
Output Mode	CW/270Hz/1kHz/2kHz
RJ45 Cable Test	
RJ45 Sequence	Support, TIA568A/568B standard
RJ45 Tracking	Optional
Others	
Operation System	Linux
Interface	2×RJ45 port, 1xUSB Type C
Optical Port	OTDR: FC/UPC or SC/UPC
	OPM: 2.5mm universal port
	VFL: 2.5mm universal port
Wireless	Wifi, Bluetooth and phone app
Display	6.2-inch Capacitive touch screen
Battery	5000mAh lithium battery
Data Storage	16G
Temperature	Working Temp: -10℃~+50℃; Storage Temp: -20℃~+70℃
Humidity	≤95% (No-condensation)
Dimension	195×141×46mm
Weight	0.9kg (with battery)

Model	Wavelength	Dynamic Range	Dead-zone
FHO3300Plus-D26	1310/1550nm±20nm	26/24dB	0.8/3.5m
FHO3300Pus-D30		30/28dB	0.8/3.5m
FHO3300Plus-D35		35/33dB	0.8/3.5m
FHO3300Plus-D38		38/36dB	0.8/3.5m
FHO3300Plus-T26F	1310/1550/1625nm±20nm	26/24/24dB	0.8/3.5m
FHO3300Plus-T30F		30/28/28dB	0.8/3.5m
FHO3300Plus-T35F		35/33/33dB	0.8/3.5m
FHO3300Plus-T38F		38/36/36dB	0.8/3.5m
FHO3300Plus-TC26F	1310/1550/1650nm±20nm	26/24/24dB	0.8/3.5m
FHO3300Plus-TC30F		30/28/28dB	0.8/3.5m
FHO3300Plus-TC35F		35/33/33dB	0.8/3.5m
FHO3300Plus-TC38F		38/36/36dB	0.8/3.5m
FHO3300Plus-MD21	850/1300/1310/1550±20nm	19/21/36/34dB	0.8/3.5m



歲望有限公司

802626 高雄市苓雅區新光路38號5樓之1
電話：07-5368282 傳真：07-5368272

WEVANT Co., Ltd.

5F.-1, No.38, Xinguang Rd., Lingya Dist.,
Kaohsiung City 802, Taiwan (R.O.C.)
TEL: +886-7-5368282 FAX: +886-7-5368272



Let's go in the grand way!