



FHP1 Series Power Meter

- Stable and reliable, sturdy and durable
- Multi-unit display dBm/dB/mw
- Support user calibration function
- Type-C USB charging port
- Support auto power off and backlight function

Items	Specifications	
	FHP-1A02	FHP-1B02
Sensor Type	InGaAs	
Connector	FC/PC	
Working Wavelength	800~1700nm	
Calibrated Wavelength	850/1300/1310/1550/1490/1625/1650nm	
Test Range	-60~+10dBm	-40~+26dBm
Resolution	0.01dB	
Accuracy	±0.35dB	
Display unit	dBm/dB/mw	
Recognizable frequency	270Hz, 1kHz, 2kHz	
Auto shutdown	Support	
Backlight	Support	
Connector	FC/UPC	
USB port	Type-C	
Power Supply	4pcs*NI-MH AAA 850mAh 1.2V rechargeable battery; DC 5V/1A	
Working Temp	-10°C~+50°C	
Storage Temp	-20°C~+70°C	
Dimension/Weight	115L×62W×30H mm / about 140g	

Let's go in the grandway!



歲望有限公司

802626 高雄市苓雅區新光路38號5樓之1
電話：07-5368282 傳真：07-5368272

WEWANT Co., Ltd.

5F.-1, No.38, Xinguang Rd., Lingya Dist.,
Kaohsiung City 802, Taiwan (R.O.C.)
TEL: +886-7-5368282 FAX: +886-7-5368272

