



### OFI-3 Fiber Identifier

- Convenient and easy to use
- LED indicator is simple and clear
- Identification of 270/1k/2k Hz modulation frequency
- Direction and intensity indication of optical signal
- Natural light intensity calibration function

Items	Specifications
Fiber Adapter	RB0.25mm, RB0.9mm, RB3.0mm
Wavelength Range	900~1650nm
Frequency	CW/270Hz/1kHz/2kHz
Sensitivity	Min -50dBm
Sensitivity	1310nm @ 0.25mm: -20dBm, 0.9mm: -20dBm, 3.0mm: -20dBm
	1550nm @ 0.25mm: -30dBm, 0.9mm: -20dBm, 3.0mm: -30dBm
Display (LED)	Signal, Direction, Frequency, Intensity(5 grades), Low battery
Power Supply	2*AA battery
Working Temp	-10°C~+50°C
Storage Temp	-20°C~+70°C
Dimension/Weight	202L×62W×38H(mm) / 300g
Accessories	2*AA battery, Adapter(RB0.25mm, RB0.9mm, RB3.0mm), Carrying bag, Quick guide, Test report

Let's go in the grandway!



歲望有限公司

802626 高雄市苓雅區新光路38號5樓之1  
電話：07-5368282 傳真：07-5368272

WEWANT Co., Ltd.

5F.-1, No.38, Xinguang Rd., Lingya Dist.,  
Kaohsiung City 802, Taiwan (R.O.C.)  
TEL: +886-7-5368282 FAX: +886-7-5368272

