

500XP PAIR TRACING PROBE

THE MOST ADVANCED PROBE ON THE MARKET

TESTING | TROUBLESHOOTING | ACCURACY

Product Features:

Dual LED Indicators: Provides real-time proportional signal strength feedback.

acAlert™ Voltage Detection (Optional): Emits audible and visible alerts if brought near wires that have AC mains power voltage.¹

Mains Power Hum Filtering: Eliminates hum noise, so you can focus on tracing the correct wire (60 Hz default, 50 Hz user selectable).

Bandpass Filters: Further reduces noise. Separate LED display with real-time signal strength indicators. Best used when combined with Tempo Tones set to 577 Hz and 983 Hz.²

Industry Standard: Works with a variety of toners (500 Hz to 2.5 kHz).

Nautilus® Environmental Protection: Environmentally protected against dust and moisture. Drop and Crush resistant.

Three Year Limited Warranty.

- Two-button operation enables the technician to quickly and easily switch modes
- Rugged and water-resistant design allows for tracing in all environments
- Improved signal fidelity helps to trace longer cable loops

Ordering Information:

CAT. NO.	DESCRIPTION
500XP	500XP Pair Tracing Probe (POS)
500XPB	500XP Pair Tracing Probe (Boxed)
HS001	Replacement Headset
500XPH	500XP with 200C Holster



TEMPO
COMMUNICATIONS

Renewed Vision. Innovation Forward.



Follow us on Social Media
[@TempoComms](#)

500XP SPECIFICATIONS



Telephone Compatibility:	Suitable for telecommunication network (TNV-3) signals. May also be used on other networks with similar maximum voltage limits.
Maximum Tip Voltage:	100V - Emits audible and visible alerts if brought near 50 - 60 Hz AC power cables (acAlert™)
Maximum Transient:	500V (1.2 / 50 μs)
Sensitivity:	Adjustable, 0 dB to ≥ 60 dB
Frequency Response:	200 Hz to 3 kHz
Crush Resistance ³ :	220 lb (100 kg)
Drop Resistance ⁴ :	10 ft (3 m)
Dust Resistance:	IP67 Rated: Total Dust Ingress Protection
Water Resistance:	IP67 Rated: Floats.
Operating Temperature:	-4 to 122°F (-20 to 50°C)
Hearing Protection:	< 103 dB SPL Peak when used with Tempo headsets
Battery Type:	9V PP3
Battery Life:	> 50 Hours

¹acAlert™ warns of the presence of hazardous voltage. The 500XP is not intended to be come in direct contact with any external power supply, but is safe up to 100V.

²Not bandpass mode; Bandpass mode is optimized for use with Tempo Communication's precision tone generators at 577 Hz & 983 Hz.

³Distributed load.

⁴Water and dust resistance cannot be guaranteed if damage to the casing occurs.



歲望有限公司

802626 高雄市苓雅區新光路38號5樓之1
電話：07-5368282 傳真：07-5368272

WEWANT Co., Ltd.

5F.-1, No.38, Xinguang Rd., Lingya Dist.,
Kaohsiung City 802, Taiwan (R.O.C.)
TEL: +886-7-5368282 FAX: +886-7-5368272

